

Site Dumpers

PAYLOAD CAPACITIES

4,409 / 13,228 lbs (2,000 / 6,000 kg)

HEAPED CAPACITIES

48.88 ft³ / 128.88 ft³ (1,384 L / 3,650 L)



FEATURES

- Payload capacities from 4,409 to 13,230 lbs (2,000 to 6,000 kg).
- Choice of power tip or power swivel 4-wheel drive models, as well as all-wheel-steer (AWS) models and straight tip, 2-wheel drive model.
- Excellent jobsite performance due to high ground clearance and flotation tires.
- Operator accessibility from either side.

- Dumping position allows complete removal of all materials. Machines can dump and back up simultaneously.
- Excellent jobsite visibility; controls are easily accessible and simple to operate.
- Kubota, Yanmar or Perkins diesel engines with electric starting.
- Totally enclosed, oil-immersed, multi-plate disc brakes.

DUMPERS

Specifications and Dimensions							
	Heaped	Maximum payload	Engine hp (kW) @ RPM	Steering type	Transmission type	Water level	Struck level
Straight Tip 2-Wh	eel Drive						
PT200	48.88 ft ³ (1,384 L)	4,409 lbs (2,000 kg)	Kubota D905E 22 hp (16.4 kW) @ 3,000	rear wheel	3/1 Manual	30.37 ft ³ (860 L)	37.15 ft ³ (1,052 L)
Power Tip 4-Whe	el Drive Articulating						
PT2000	54.74 ft ³ (1,720 L)	4,409 lbs (2,000 kg)	Kubota D1703M 32.6 hp (24.5 kW) @ 2,600	articulated	3/1 Manual	32.14 ft ³ (900 L)	38.14 ft ³ (1,320 L)
PT4000	86.98 ft ³ (2,640 L)	8,820 lbs (4,000 kg)	Yanmar 4TNE88 38.5 hp (28.8 kW) @ 2,400	articulated	2/2 Hydrostatic	50.01 ft ³ (1,420 L)	64.98 ft ³ (2,000 L)
PT6000	115.9 ft ³ (3,780 L)	13,228 lbs (6,000 kg)	Perkins 1004C-4 80 hp (61.5 kW) @ 2,200	articulated	4/4 Powershift	69.92 ft ³ (1,950 L)	90.94 ft ³ (2,740 L)
PT6-AWS	128.88 ft ³ (3,650 L)	13,230 lbs (6,000 kg)	Perkins 1004C-44 80 hp (60.0 kW)	all wheel	4/4 Powershift	67.44 ft ³ (1,910 L)	98.87 ft ³ (2,800 L)
	Vheel Drive Articulatin	-	1/ L L M0000 M		0/4	00.0 (12	40.04.69
PS3000	65.33 ft ³ (1,850 L)	6,615 lbs (3,000 kg)	Kubota V2203-M 43.2 hp (32.4 kW) @ 2,600	articulated	3/1 Manual	33.9 ft ³ (960 L)	40.61 ft ³ (1,150 L)
PS6-AWS	117.23 ft ³ (3,320 L)	13,228 lbs (6,000 kg)	Perkins 1004C-44 82 hp (61.5 kW) @ 2,200	all wheel	4/4 Powershift	71.68 ft ³ (2,030 L)	94.63 ft ³ (2,680 L)





TEREX Construction Americas

8800 Rostin Road Southaven, MS 38671 USA TEL 662-393-1800 SALES 866-837-3923 PARTS & TECH SUPPORT 888-201-6008

FAX 662-393-1700 EMAIL sales@terexca.com WEB terexca.com

TEREX Light Construction

 590 Huey Road
 TEL
 803-324-3011

 P.O. Box 3147
 TOLL FREE
 800-433-3026

 Rock Hill, SC 29732
 FAX
 803-366-1101

 USA
 EMAIL
 sales@terexlight.com

 WEB
 www.terex.com

For more information, product demonstration, or details on purchase, lease and rental plans, please contact your local TEREX Distributor.

Effective date: October 1, 2005. For further information, please contact your local distributor or the TEREX sales office listed. Product specifications are subject to change without notice or obligation. The photographs and drawings in this brochure are for illustrative purposes only. Refer to the appropriate Operator's Manual for instructions on the proper use of this equipment. Failure to follow the appropriate Operator's Manual when using our equipment or to otherwise act irresponsibly may result in serious injury or death. Prices and specifications subject to change without notice. The only warranty applicable is the standard written warranty applicable to the particular product and sale. TEREX makes no other warranty, expressed or implied. Products and services listed may be trademarks, service marks or trade-names of TEREX Corporation and/or its subsidiaries in the USA and other countries and all rights are reserved. "TEREX" is a Registered Trademark of TEREX Corporation in the USA and many other countries. Copyright ©2005 TEREX Corporation